

Higher productivity with enhanced smart touch panel



- High-speed printing of 43 ppm
- 2-sided scanning capability with up to 70 ppm
- ✓ High-capacity paper feed of up to 2,300 sheets
- Productivity Rich media support including A5 & A6 paper sizes
- 5-inch colour touch panel
- ✓ One-touch execution for convenience
- Small footprint for desktop configuration
- Function customisation for different types of verticals
- Protection from information leakages and external attacks
- ✓ Operate MFD with mobile wirelessly
- Reduce risk of information leakages with authentication

Security & Mobility



Bringing security to the next level

imageRUNNER 1643i series comes equipped with TLS encrypted communication, IPSec communication as well as IEEE 802.1X to enhance network security and device protection through system verification.

Better visibility & operability with 5-inch colour Touch Panel



Illustration display

• Easy navigation of functions through visual guides displayed on the touch panel.



On-screen keyboard

• Greater convenience when entering texts.



Thumbnail preview

• To ensure the correct files are chosen to reduce paper wastage.

Improve work efficiency with one-touch solutions from Application Library

Save time and improve work efficiency by automating routine tasks with customisable buttons, allowing various tasks to be executed with just a click of a button.





For Hospitals / Clinics

- Photocopy appointment cards.
- Save copies of health insurance cards.
- Retrieve prescription and medical referral letter.





For Retail Stores

- Print order forms.
- Send invoices to customers.
- Send order forms via email.





For Small Offices

- Send to shared folders.
- Display bulletin board in screen saver mode.
- Send reports to head office via email.

Easily digitise documents for quicker archiving & space saving



Searchable PDF function

• Canon's technology processes the scanned file with its OCR function, recognises the text in the file and makes it text-searchable.



Compact PDF files

 Scans texts and photos in high quality while keeping the file size small in high compression mode.



Send function

 Send to multiple destinations such as emai or network folder

Cloud-based print management solution

- Provides print, copy, scan and fax usage reports.
- Offers greater usage and print optimisation through reporting and usage analytics.



Track Print, Scan and Copy costs





SPECIFICATIONS





Main unit		iR1643iF	iR1643i	Copy specifications	iR1643iF	iR1643i
Machine type		Monochrome A4 Laser Multifunctional		Copy speed	43 ppm (A4)	
Core functions		iR1643iF: Print, Copy, Scan, Send and Fax iR1643i: Print, Copy, Scan and Send		First-copy-out time (BW)	Platen: Approximately 6.3 seconds or less ADF: Approximately 6.4 seconds or less	
Control panel		12.7 cm (5-inch) TFT LCD WVGA Colour Touch panel		Copy resolution (dpi)	Reading: 600 x 600 Printing: 600 x 600	
lemory		Standard: 1GB RAM		Multiple copies	Up to 999 copies	
Interface connection	Network	1000Base-T / 100Base-TX / 10Base-T, Wireless LAN (IEEE802.11 b / g / n), Wi-Fi Direct Connection, NFC	1000Base-T/ / 100Base-TX / 10Base-T, Wireless LAN (IEEE802.11 b / g / n), Wi-Fi Direct Connection	Magnification	25% - 400% (1% increment)	
				Preset reductions	25%, 50%, 70%, 81%, 86%	
				Preset enlargements	115%, 122%, 141%, 200%, 4	100%
	Others	USB 2.0 (Host) x2, USB 2.0 (Device) x1		Scan specifications		
		USB Memory		o and spot in tall on s		
etwork security		IP / Mac Address Filtering, IPSec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP		Document feeder type (A4, 80gsm)	1 PDS	
				Paper capacity	A4: 50 sheets (80 gsm)	
ocument security		Secure Print, Encrypted PDF, De	vice Signature PDF	Supported media sizes	Standard size: A4R, B5R, A5R,	
aper supply	Standard	Paper Cassette: 550 sheets			Custom size: 105 × 128 mm to	215.9 x 355.6 mm
pacity	o curraci a	Multi-purpose tray: 100 sheets 2,300 sheets (with PAPER FEEDER PF-C1x3)		Scan speed (ipm: BW / Colour; A4)	Copy: 1-sided Scanning: 20 2-sided Scanning: 34 Send: 1-sided Scanning (BW / Colour): 38 / 13	
(A4, 80gsm)	Maximum					
Paper output capacity (A4, 80gsm)		150 sheets		Scan resolution (dpi)	2-sided Scanning (BW / Colour): 70 / 26 Copy: 600 x 600	
Toner (Estimated yield @ 5% coverage)		Toner T06 Black: 20,500 impressions (A4)		Scan resolution (upi)	Send: (Push, Pull) up to 600 x 600 Fax: up to 600 x 600	
Supported media sizes	Upper cassette 1	Standard size: A4, B5, A5, A5R, A6 Custom size: Minimum 105 x 148 mm up to 216 x 355.6 mm		Pull scan specifications	ScanGear MF for both TWAIN and WIA	
	Multi-purpose	e Standard size: A4, B5, A5, A5R, A6, Index Card,		Send specifications		
	tray	Envelopes [No. 10 (COM 10), Monarch, ISO-C5, DL] Custom size: Minimum 76.2 x 127 mm up to 216 x 355.6 mm		Destination	Email / I-Fax (SMTP), SMB, FTP	
pported	Upper	60 to 120 gsm		Address book	LDAP (50) / Local (300) / One touch (281)	
media weights	cassette 1	e 60 to 199 qsm		Send resolution (dpi)	Push: 196 x 204 (I-Fax), 300 x 300 (Email / SMB / FTP) Pull: Max. 9,600 x 9,600 File: FTP, SMB Email / I-Fax: SMTP, POP3, I-Fax (Simple)	
	tray	(0), 100				
	Duplex	60 to 120 gsm		Communication protocol		
Warm-up time		From power on: 14 seconds or less* *Time from device power-on until copy ready (not print reservation) From sleep mode: 4 seconds or less		File format	TIFF, JPEG, PDF (Compact, searchable, encrypted, digital signature)	
Dimensions (W x D x H)		494 x 595 x 452 mm (with the multi-purpose tray extended)	480 x 595 x 452 mm (with the multi-purpose tray extended)	Fax specifications		
Installation space (W x D) Weight		708 x 1,105 mm (with cassette open + 100 mm gap	694 x 1,105 mm (with cassette open + 100 mm gap	Maximum number of connection lines	1	N/A
		around the main body)	around the main body)	Modem speed	Super G3: 33.6 kbps G3: 14.4 kbps	N/A
		Approximately 19 kg without to	ner	Compression method	MH, MR, MMR, JBIG	N/A
Print specifications Print speed (BW)		43 ppm (A4)		Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine / Photo), 200 x 100 (Normal)	N/A
rint resolution (d	lni)	600 × 600		FAX memory	Up to 512 pages	N/A
	Standard		LIED II DCI 6 DCI E	One touch	Max. 281	N/A
Page description languages	Stanuaru	UFR II, PCL6, PCL5, Adobe® PostScript® 3™	UFR II, PCL6, PCL5	Group dials	Max. 299	N/A N/A
	Optional		Adobe® PostScript® 3™	Sequential broadcast	Max. 310 addresses	N/A
irect print	Ориона	Direct printing available from	USB memory and LPR	Sequential broadcast	Wax. 510 addresses	IN/A
Fonts		Supported file types: TIFF, JPEG, PDF and XPS (only LPR) PCL fonts: 93 Roman		Environmental specification	ions	
		PS fonts: 136 Roman		Power source	AC220-240V: 3.9A, 50 / 60Hz	
Operating system (UFR II / PCL / PS)		Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, Mac OS X (10.9 or later)		Power consumption	Maximum: Approx. 1,420W or less	
				Paper supply options		
				PAPER FEEDER PF-C1	Paper capacity: 550 sheets (Paper size: A4, B5, A5, A5R, Custom size: 105 x 148 mm Dimensions (W x D x H): 480 to the main unit) Weight: Approximately 4.0 l	A6 to 216 x 355.6 mm) x 464 x 842* mm (*att

Other optional accessories

COPY CARD READER-F1, PS PRT KIT-CB1 AS, BARCODE PRT KIT-E1, CONTROL I/F KIT-C1

Weight: Approximately 4.0 kg



SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #15-10, Galaxis, Singapore 138522

Delighting You Always 1 Fusionopolis Flace, #15-10, Guilland, July 1997 | www.canon-asia.com This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document. Canon and Business Can Be Simple are trademarks of Canon Inc, and/or its affiliates. Other names may be the trademarks for their respective owners.

