


imageRUNNER
2645i / 2635i / 2630i / 2625i

Canon

Delighting You Always

imageRUNNER SERIES REDEFINED

Transform The Way You Work



Print Up to 45 ppm

7-inch Colour Touch Panel

Mobile Print Ready

Business Can Be Simple

THE NEW iR2600i SERIES

GREATER PEACE OF MIND WITH PERFORMANCE RELIABILITY



Highly **robust** machine



Enhanced **functionalities**



Improved **performance**



BOOSTED PRODUCTIVITY WITH HIGHER USABILITY



1 Higher operability with 7-inch colour touch panel

- Navigate easily with touch operations similar to a smartphone, such as flick, drag-and-drop.

2 Smart and sophisticated design

- Save time with quick selection and execution of last 10 used functions.

3 Fully customisable functions


- Personalise print functions and individual user settings to simplify workflows and increase productivity.



MOBILE PRINTING

iR2600i series supports a wide range of mobile applications, ranging from Canon PRINT Business, Apple® AirPrint®, Google Cloud Print™, Mopria® and Canon Print Service. Printing or scanning from a mobile device has never been easier.

IMPROVED CONNECTIVITY BETWEEN OFFICE IT EQUIPMENT



A POWERFUL AND SECURE MULTI-FUNCTIONAL PRINTER FOR YOUR BUSINESS



Provide security measures based on your needs

- Enjoy greater document security with Encrypted PDF, Device signature PDF and optional User signature PDF.
- Secure office environment with available network security functions such as SNMP v3, IEEE 802.1x and dual network.



Manage your prints with uniFLOW Online Express

- Prevent unauthorised prints by limiting access with authentication.
- Track usage and manage costs with an intuitive dashboard supported by personalised widgets.
- Prevent unintended or incorrect outputs when paired with forced-hold print feature, to temporarily hold documents in each device.



Convert paper files to electronic data easily

- Convert paper originals into electronic data, including Microsoft PowerPoint* (.pptx format) and Word* (.docx format) so work can be done with an easily editable format.
- Retain document style while creating text searchable* documents, reducing the need for manual input.

*Optional

SPECIFICATIONS

Main unit	
Machine type	A3 Monochrome Laser Multifunctional
Core functions	Print, Copy, Scan, Send and Optional Fax
Control panel	Standard: 7-inch TFT LCD WVGA Colour Touch panel
Memory	Standard: 2.0GB RAM
Interface Connection	Network: 1000Base-T / 100Base-TX / 10Base-T, Wireless LAN (IEEE 802.11 b / g / n) Others: USB 2.0 (Host) x3, USB 2.0 (Device) x1
Print / Copy speed	iR 2645i: 45 ppm (A4), 22 ppm (A3) iR 2635i: 35 ppm (A4), 22 ppm (A3) iR 2630i: 30 ppm (A4), 15 ppm (A3) iR 2625i: 25 ppm (A4), 15 ppm (A3)
Memory media	Standard: USB memory
Paper supply capacity (A4, 80gsm)	Standard: 1,200 sheets Maximum: 2,300 sheets (with Cassette Feeding Unit-AN1)
Paper output capacity (A4, 80gsm)	Standard: 250 sheets Maximum: 545 sheets (with Inner Finisher-J1)
Supported media weights	Paper cassettes (1 / 2): 60 to 128 gsm Multi-purpose tray: 52 to 220 gsm (Thin vertical grain paper feed only: 52 to 59 gsm) Duplex: 60 to 105 gsm
Warm-up time (Quick start mode: ON)	From power-on: 12 seconds or less* From sleep mode: 10 seconds or less *Time from power-on, until copy ready
Dimensions (W x D x H)	iR 2645i / 2635i: 586 x 709 x 926 mm (with DADF-BA1)* iR 2630i / 2625i: 586 x 713 x 912 mm (with DADF-AZ1)* iR 2625i: 586 x 700 x 818 mm (with Platen Cover type Z) *With the multi purpose tray extended
Weight	Standard: iR 2645i / 2635i: Approximately 68.3 kg without toner iR 2630i / 2625i: Approximately 66.8 kg without toner
Power source	220-240 V, 5.2 Amp
Power consumption	Maximum: Approximately 1,500W Standby: Approximately 20W Sleep mode: Approximately 0.6W

Print specifications	
Print resolution (dpi)	1,200 x 1,200
Page description language	Standard: UFR II, PCL 6 Optional: Genuine Adobe® PostScript® 3™
Operating system	UFR II: Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019, MAC OS X (10.9 or later) PCL: Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019 PS: Windows® 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019, MAC OS X (10.9 or later) PPD: Windows® 7 / 8.1 / 10, MAC OS X (10.9 or later)

Copy specifications	
First-Copy-Out Time (A4)	iR 2645i / 2635i: Approximately 3.9 seconds or less iR 2630i / 2625i: Approximately 5.9 seconds or less
Copy resolution (dpi)	Reading: 600 x 600 Printing: Up to 1,200 x 1,200
Multiple copies	Up to 9,999 copies

Send specifications	
Destination	Email / I-Fax (SMTP), SMB, FTP, WebDAV, Super G3 FAX (Optional)
Address book	LDAP (2,000) / Local (1,600) / One-touch (200)
Send resolution (dpi)	Push: 600 x 600 Pull: 600 x 600, 400 x 400, 300 x 300, 200 x 200, 150 x 150, 75 x 75
Communication protocol	File: FTP (TCP / IP), SMB (TCP / IP), WebDAV Email / I-Fax: SMTP (Send), POP3 (Receive)
File format	Standard: TIFF (MMR), JPEG*, PDF (Compact, PDF A / 1-b, Encrypted), XPS (Compact), PDF / XPS (Device signature) Optional: PDF (Trace & smooth), PDF / XPS (User signature, Searchable), Office Open XML (PowerPoint, Word) *Single page only

Scan specifications	
Selectable type (Optional)	iR2645i / 2635i: Document Feeder (DADF-BA1) or Platen Cover Type Y iR2630i / 2625i: Document Feeder (DADF-AZ1) or Platen Cover Type Z
Document feeder paper capacity (80 gsm)	DADF-BA1: 100 sheets DADF-AZ1: 50 sheets
Scan speed (ipm: BW / CL; A4)	DADF-BA1: 1-sided scanning: 55 / 55 (BW / CL; 300 dpi), 45 (BW; 600 dpi) 2-sided scanning: 27.5 / 27.5 (BW / CL; 300 dpi), 22.5 (BW; 600 dpi) DADF-AZ1: 1-sided scanning: 35 / 25 (BW / CL; 300 dpi), 25 (BW; 600 dpi) 2-sided scanning: 12 / 8 (BW / CL; 300 dpi), 8 (BW; 600 dpi)
Scan resolution (dpi)	Copy: 600 x 600 Send: (Push) Up to 600 x 600, (Pull) Up to 600 x 600 Fax: Up to 600 x 600
Pull scan specifications	Colour Network ScanGear2 for both TWAIN and WIA

Fax specifications	
Optional / standard	Optional on all models
Maximum number of connection lines	1
Modem speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine / Photo), 200 x 100 (Normal)
Fax memory	Up to 30,000 pages
Speed dials	Max. 200
Group dials / destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes

Security specifications	
Authentication	Standard: uniFLOW Online Express, User Authentication, Department ID Authentication, Access Management System, Picture Login Optional: My Print Anywhere secure print (Requires uniFLOW)
Network	Standard: IP / Mac address filtering, IPSEC, TLS encrypted communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP authentication, POP authentication before SMTP, S/MIME
Document	Standard: Secure print, Encrypted PDF, Encrypted secure print, Device signature Optional: User signature

Consumables	
Toner cartridge/s	NPG-84 Toner Black
Toner (Estimated yield @ 6% coverage)	Black: 30,000 impressions (A4)

Paper supply options	
Cassette Feeding Unit-AN1	Paper Capacity: 550 sheets x 2 (80 gsm) Paper Type: Thin, Plain, Thick, Colour, Recycled, Pre-punched Paper Size: A3, A4, A4R, A5R, B4, B5, B5R Custom size: 139.7 x 182 to 297 x 431.8 mm Paper Weight: 60 to 128 gsm Power Source: From the main unit Dimensions (W x D x H): 565 x 650 x 248 mm (attached to the main unit) Weight: Approximately 23.5 kg

Other accessories and supplies	
Envelope Feeder Attachment-D1, Inner 2Way Tray-L1, Inner Finisher-J1, Copy Card Reader-F1, IC Card Reader Box-C2, Copy Card Reader Attachment-H3, Utility Tray-B1, Document Tray-J1, Platen Cover Type Z, Platen Cover Type Y, DADF-AZ1, DADF-BA1, PCL International Font Set-A1, PS Printer Kit-BT1, Universal Send Digital User Signature Kit-C1, Universal Send Advanced Feature Set-H1, Barcode Printing Kit-D1, Copy Control Interface Kit-D1, Super G3 Fax Board-AV2, Remote Fax Kit-A1, ADF Access Handle-A1, Staple-P1	