

imageRUNNER | 4751i 4735i  
ADVANCE DX | 4745i 4725i

**Canon**

Delighting You Always

## Robust and reliable, with outstanding performance

The imageRUNNER ADVANCE DX 4700i series offers a wide range of solution for the modern day office in its compact design. This highly dependable series is ideal to fulfill daily office tasks.



### WORKFLOW EFFICIENCY

- Intuitive touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Industry leading Single-Pass document feeder option to allow up to 270 ipm scanning, supports paper skew prevention and comes with advanced anti-dust/streak measures.
- My ADVANCE enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.
- Intelligent Recovery wakes device from sleep mode when user is approaching device via motion sensor technology.
- Various finishing functions such as Staple-on-Demand, ECO-Staple, saddle stitch, double/corner stapling and foldings are available as an option.

### COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, resulting in lower total document cost.
- Seamless integration with output management solutions, such as uniFLOW or uniFLOW Online Express for detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.

**Business Can Be Simple**

## QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies contribute to high-quality output to meet the needs of busy department.
- State-of-the-art imaging technologies and toner allow for consistent images in rich black-and-white tones and 1,200-dpi print resolution.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Standard PCL and optional Adobe® PostScript® 3™ print driver allows seamless integration with enterprise applications.
- Remote diagnostics allow timely, accurate and effective resolution.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

## SUSTAINABILITY

- Fusing technologies and innovative sleep mode features help lower overall energy consumption.
- Minimise paper wastage by holding jobs at the device with Force Hold Print. Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.
- Consumes as little as 0.9W in sleep mode.

## SECURITY

- Control who has access to the device with different authentication methods such as picture login, department ID, user authentication and card access.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.
- Ensure device is safe from unknown firmware installation with system verification at startup.
- Integrate with third-party solutions for complete monitoring protection.

# MACHINE SPECIFICATION

## MAIN UNIT

**Type**  
A3 Monochrome Laser Multifunctional

**Core Function**  
Print, Copy, Scan, Send, Store and Optional Fax

**Processor**  
Canon Dual Custom Processor (Shared)

**Control Panel**  
Standard:10.1" TFT LCD WSVGA Colour Touch panel

**Memory**  
Standard : 3.0GB RAM

**Hard Disk drive**  
Standard\*: 320GB (Available Disk Space: 250GB)  
Maximum : 1TB  
\*A different initial HDD may be used.

**Mirroring Hard Disk Drive:** Optional

**Interface Connection**  
**Network** Standard: 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)  
Optional : NFC, Bluetooth Low Energy  
**Others** Standard : USB 2.0 x1 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)  
Optional : Serial Interface, Copy Control Interface

**Paper Supply Capacity (A4, 80gsm)**  
Standard : 1,200 sheets (2x 550-sheet cassette,  
1x 100-sheet multi-purpose tray)  
Maximum : 6,350 sheets (with High Capacity Cassette  
Feeding Unit-B1 and Paper Deck Unit-F1)

**Paper Output Capacity (A4, 80gsm)**  
Standard : 250 Sheets  
Maximum : 3,350 Sheets (with Buffer Pass-N1 +  
Staple Finisher-Y1 or Booklet Finisher-Y1)

**Finishing Capabilities**  
Standard : Collate, Group  
With options : Collate, Group, Offset, Staple, Saddle Stitch,  
Hole Punch, ECO Staple, Staple-On-Demand

**Supported Media Types**  
**Multi-Purpose Tray:**  
Thin, Plain, Heavy, Colour, Recycled, Pre-punched,  
Transparency, Tracing, Label, Bond, Envelope  
**Paper Cassette (1/2):**  
Thin, Plain, Heavy, Colour, Recycled, Pre-punched

**Supported Media Sizes**  
**Multi-Purpose Tray:**  
Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R,  
Foolscap, India Legal, F4A  
Custom Size: 98.0 x 148.0 mm to 297.0 x 431.8 mm  
Free size: 98.0 x 148.0 mm to 297.0 x 431.8 mm  
Envelope: COM10 No.10, Monarch, DL, ISO-C5  
Envelope custom size: 98.0 x 148.0mm to 297.0 x 431.8mm  
**Paper Cassette 1:**  
Standard size : A4, A4R, A5R, B4, B5, B5R, Foolscap,  
India Legal, F4A  
Custom size : 139.7 x 182.0 mm to 297.0 x 390.0 mm

**Paper Cassette 2:**  
Standard size : A3, A4, A4R, A5R, B4, B5, B5R, Foolscap,  
India Legal, F4A  
Custom size : 139.7 x 182.0 mm to 297.0 x 431.8 mm  
Envelope\* : COM10 No.10, Monarch, DL, ISO-C5  
\* Envelope Feeder Attachment-D1 is required.

**Supported Media Weights**  
Multi-purpose tray : 52 to 220 gsm  
(Thin (52 to 59gsm):vertical grain paper feed only)  
Paper Cassette (1/2) : 60 to 220 gsm  
Duplex : 60 to 105 gsm

**Warm-up Time**  
Quick Startup Mode : 4 seconds or less\*  
From Sleep Mode : 10 Seconds or Less  
From Power On : 24 Seconds or Less\*  
+ Time from device power-on to when the copy icon appears and is enabled to  
operate on the touch panel display.  
\* Time from device power-on, until copy ready (not print reservation)

**Dimensions (W x D x H)**  
With Platen Cover-Y2 : 608 x 713 x 822 mm  
With Single Pass DADF-C1 : 608 x 722 x 932 mm  
With DADF-BA1 : 608 x 719 x 926 mm

**Installation Space (W x D)**  
Basic: 1,116 x 1,160 mm (with Platen Cover Type Y2 + Multi-  
purpose tray open/extension tray extended +  
Paper Cassette open)  
1,116 x 1,169 mm (with Single Pass DADF-C1 + Multi-  
purpose tray open/extension tray extended +  
Paper Cassette open)  
1,116 x 1,166 mm (with DADF-BA1 + Multi-purpose tray  
open/extension tray extended + Paper Cassette open)  
Fully Configured:  
1,811 x 1,169 mm (with Single Pass DADF-C1 + Paper Deck  
Unit-F1 + Booklet Finisher-Y1 with extension tray extended  
and Saddle unit drawn)  
1,811 x 1,166 mm (with DADF-BA1 + Paper Deck Unit F1  
+ Booklet Finisher-Y1 with extension tray extended and  
Saddle unit drawn)

**Weight**  
**iR-ADV DX 4751i/4745i/4735i :**  
With Platen Cover-Y2 : Approx. 76.1 kg including toner  
With Single Pass DADF-C1 : Approx. 89.0 kg including toner  
With DADF-BA1 : Approx. 82.5 kg including toner  
**iR-ADV DX 4725i:**  
With Platen Cover-Y2 : Approx. 75.0 kg including toner  
With Single Pass DADF-C1 : Approx. 87.9 kg including toner  
With DADF-BA1 : Approx. 81.4 kg including toner

## Printing Specifications

**Print Speed**  
iR-ADV DX 4751i : Up to 51 ppm (A4), Up to 37 ppm (A4R),  
Up to 25 ppm (A3), Up to 20 ppm (A5R)  
iR-ADV DX 4745i: Up to 45 ppm (A4), Up to 32 ppm (A4R),  
Up to 22 ppm (A3), Up to 20 ppm (A5R)  
iR-ADV DX 4735i: Up to 35 ppm (A4), Up to 32 ppm (A4R),  
Up to 22 ppm (A3), Up to 20 ppm (A5R)  
iR-ADV DX 4725i: Up to 25 ppm (A4), Up to 17 ppm (A4R),  
Up to 15 ppm (A3), Up to 17 ppm (A5R)

**Print Resolution (dpi):** 1,200 x 1,200

**Page Description Languages**  
Standard : UFR II, PCL 6  
Optional : Adobe®PostScript®3™

**Direct Print**  
Supported file types: PDF, EPS, TIFF/JPEG, and XPS

**Printing From Mobile and Cloud**  
AirPrint, Mopria, Google Cloud Print, Canon Print Business  
and uniFLOW Online

A range of software and MEAP-based solutions are available  
to provide printing from mobile devices or internet-  
connected devices and cloud-based services depending on  
your requirements.

Please contact your sales representative for further  
information

**Fonts**  
PS fonts: 136 Roman  
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT J/K/S/T<sup>1</sup> (Japanese, Korean,  
Simplified and Traditional Chinese),  
Barcode fonts<sup>2</sup>

<sup>1</sup> Requires optional PCL INTERNATIONAL FONT SET-A1  
<sup>2</sup> Requires optional BARCODE PRINTING KIT-D1

**Operating System**  
UFR II: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016/Server 2019,  
MAC OS X (10.10 or later)  
PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016/Server 2019  
PS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016/Server 2019,  
MAC OS X (10.10 or later)  
PPD: Windows® 7/8.1/10, MAC OS X (10.9 or later)

## Copy Specifications

iR-ADV DX 4751i : Up to 51 ppm (A4), Up to 37 ppm (A4R),  
Up to 25 ppm (A3), Up to 20 ppm (A5R)  
iR-ADV DX 4745i: Up to 45 ppm (A4), Up to 32 ppm (A4R),  
Up to 22 ppm (A3), Up to 20 ppm (A5R)  
iR-ADV DX 4735i: Up to 35 ppm (A4), Up to 32 ppm (A4R),  
Up to 22 ppm (A3), Up to 20 ppm (A5R)  
iR-ADV DX 4725i: Up to 25 ppm (A4), Up to 17 ppm (A4R),  
Up to 15 ppm (A3), Up to 17 ppm (A5R)

**First-Copy-Out Time (A4)**  
iR-ADV DX 4751i : Approx. 3.7 seconds or less  
iR-ADV DX 4745i/4735i : Approx. 3.8 seconds or less  
iR-ADV DX 4725i : Approx. 5.2 seconds or less

**Copy Resolution (dpi)** 600 x 600  
**Multiple Copies** Up to 9,999 copies  
**Copy Density** Automatic or Manual (9 Levels)  
**Magnification**  
Variable zoom: 25% - 400% (1% Increments)  
Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%,  
86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%

## Scan Specifications

Type	
Standard	: Colour Flatbed Scan Unit
Optional	: Platen Cover Type-Y2, Single Pass DADF-C1* or DADF-BA1 [2-sided to 2-sided (Automatic with DADF)]
	* Detect Feeder Multi Sheet Feed is supported.

### Document Feeder Paper Capacity (80gsm)

Single Pass DADF-C1	: up to 200 sheets
DADF-BA1	: up to 100sheets

### Acceptable Originals and Weights

Platen: Sheet, Book, and 3-Dimensional objects

Document Feeder media weight:

SINGLE PASS DADF-C1\*:

1-sided scanning : 38 to 220 gsm (BW, CL)

2-sided scanning : 38 to 220 gsm (BW, CL)

\*Acceptable weights of A6R or smaller is 50 to 220gsm.

DADF-BA1:

1-sided scanning : 38 to 128 gsm (BW), 64 to 128 gsm (CL)

2-sided scanning : 50 to 128 gsm (BW), 64 to 128 gsm (CL)

### Supported Media Sizes

Platen: max. scanning size: up to 297.0 x 431.8 mm

Document Feeder media size:

Single Pass DADF-C1: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R,

Custom size: 70.0 x 139.7 mm to 304.8 x 431.8 mm

DADF-BA1: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6,

Custom size: 139.7 x 128 mm to 297.0 x 431.8 mm

### Scan Speed (ipm: BW/CL; A4)

Single Pass DADF-C1:

1-sided Scanning : 135/135 (300 x 300 dpi, send),  
80/80 (600 x 600 dpi, copy)

2-sided Scanning : 270/270 (300 x 300 dpi, send),  
160/90 (600 x 600 dpi, copy)

DADF-BA1:

1-sided Scanning : 70/70 (300 x 300 dpi, send),  
51/51 (600 x 600 dpi, copy)

2-sided Scanning : 35/35 (300 x 300 dpi, send),  
25.5/25.5 (600 x 600 dpi, copy)

### Scan Resolution (dpi)

Scan for Copy : 600 x 600

Scan for Send : (Push) 600 x 600 (SMB/FTP/WebDAV/  
iFAX), (Pull) 600 x 600

Scan for Fax : 600 x 600

### Pull Scan Spec

Colour Network ScanGear2. For both TWAIN and WIA

Supported OS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

## Send Specifications

### Destination

Standard : E-mail/Internet FAX (SMTP), SMB 3.0, FTP,  
WebDAV, Mail Box

Optional : Super G3 FAX, IP Fax

### Address Book

LDAP (2,000)/Local (1,600)/One-touch (200)

### Send Resolution (dpi)

Push : up to 600 x 600

Pull : up to 600 x 600

### Communication Protocol

File : FTP (TCP/IP), SMB3.0 (TCP/IP), WebDAV

E-mail/I-Fax : SMTP, POP3

### File Format

Standard : TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

## Fax Specifications

### Maximum Number of Connection Lines 4

Modem Speed : Super G3 : 33.6 kbps  
G3 : 14.4 kbps

Compression Method : MH, MR, MMR, JBIG

### Resolution (dpi):

400x400 (Ultra Fine), 200x400 (Super Fine),  
200x200 (Fine), 200x100 (Normal)

### Sending/Receiving Size

Sending : A3, A4, A4R, A5\*, A5R\*, B4, B5\*, B5R\*

Receiving : A3, A4, A4R, A5R, B4, B5, B5R

\*1 Sent as A4 \*2 Sent as B4 short

FAX Memory : Up to 30,000 pages (2,000 jobs)

Speed Dials : Max. 200

Group Dials/Destinations : Max. 199 dials

Sequential Broadcast : Max. 256 addresses

Memory Backup : Yes

## Store Specifications

### Mail Box (Number supported)

100 User Inboxes, 1 Memory RX Inbox,  
50 Confidential Fax Inboxes  
Maximum 30,000 Pages (2,000 jobs) Stored

### Advanced Box

Communication Protocol: SMB or WebDAV  
Supported Client PC: Windows® 8.1/10  
Concurrent Connections (Max.): SMB: 64, WebDAV: 3

### Advanced Box available disc space

Standard: 16GB  
(With option: max. 480GB)

## Security Specifications

### Authentication

Standard : User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)

### Document Security

**Print Security** (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print\*)

**Receive Data Security** (Confidential Fax Inbox Forwarding Received Documents Automatically)

**Scan Security** (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control)

**Send Data Security** (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Scan Lock (QR code), Document Tracking (Secure Watermark)

\*1 Requires uniFLOW Online/uniFLOW

### Network Security

TLS 1.3, IPSec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface)

### Device Security

Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection),  
Optional: IEEE2600.2 (Common Criteria Certification) (available at a later schedule)

### Device Management and Auditing

Administrator Password, Digital Certificate And Key Management, Audit Log,  
Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

## Environmental Specifications

### Operating Environment

Temperature: 10 to 30 °C

Humidity: 20 to 80 % RH (Relative Humidity)

Power Source : 220-240V, 50-60Hz, 5.6A

### Power Consumption

Maximum: 1,500W

Standby: Approx. 38 W\*1

Sleep mode: Approx. 0.9 W\*2

\*1 Reference Value (measured one unit)

\*2 0.9W sleep mode is not available in all circumstances due to certain settings.

## Consumables

Toner Cartridge : NPG-73 Toner BK  
Toner Yield (Estimated Yield @6% Coverage)  
NPG-73 Toner BK : 42,100 pages

## Software and Printer Management

### Tracking and reporting

Universal Login Manager (ULM)  
uniFLOW Online Express

### Remote Management Tools

iW Management Console  
eMaintenance  
Content Delivery System

### Scanning Software

Network ScanGear

## Optimisation Tools

Canon Driver Configuration Tool  
NetSpot Device Installer

## Platform

MEAP (Multifunctional Embedded Application Platform)

## Document Publishing

IW DESKTOP

## Paper Supply Options

### CASSETTE FEEDING UNIT - AN1

Paper Capacity : 550 Sheets x 2 (80gsm)  
Paper Type : Thin, Plain, Heavy, Colour, Recycled,  
Pre-punched  
Paper Size : A3, A4, A4R, A5R, B4, B5, B5R,  
Custom size : 139.7 x 182.0 mm to 297.0 to 390.0 mm  
Paper Weight : 60 to 220 gsm  
Power Source : From the Main Unit  
Dimensions (WxDxH) : 565 x 650 x 248 mm  
(attached to the main unit)  
Weight : Approx. 23.5 kg

### HIGH CAPACITY CASSETTE FEEDING UNIT - B1

Paper Capacity : 2,450 sheets (80 gsm)  
Paper Type : Thin, Plain, Heavy, Colour, Recycled,  
Pre-punched  
Paper Size : A4  
Paper Weight : 60 to 220 gsm  
Power Source : From the Main Unit  
Dimensions (WxDxH) : 565 x 650 x 248 mm  
(attached to the main unit)  
Weight : Approx. 28 kg

### PAPER DECK UNIT - F1

Paper Capacity : 2,700 sheets (80 gsm)  
Paper Type : Thin, Plain, Heavy, Colour, Recycled,  
Pre-punched  
Paper Size : A4, B5  
Paper Weight : 60 to 128 gsm  
Power Source : From the Main Unit  
Dimensions (W x D x H) : 344 x 630 x 440 mm  
(attached to the main unit)  
Weight : Approx. 31 kg

## Hardware Accessories

### Card Readers

COPY CARD READER-F1  
COPY CARD READER ATTACHMENT-B7

### Others

PLATEN COVER TYPE-Y2  
ENVELOPE FEEDER ATTACHMENT KIT-D1  
UTILITY TRAY-B1  
NUMERIC KEYPAD-A1

## Security Options

### Device Security

iR-ADV SECURITY KIT-AN1 FOR IEEE 2600 COMMON  
CRITERIA CERTIFICATION  
(available at a later schedule)

### Data Security

HDD MIRRORING KIT-J1  
2.5INCH/250GB HDD-N1  
2.5INCH/1TB HDD-P1

## System and Controller Options

### Print Accessories

PCL INTERNATIONAL FONT SET-A1  
PCL ASIAN FONT SET-A1  
PS PRINTER KIT-BG1/CC1

### Barcode Printing

BARCODE PRINTING KIT-D1

### System Accessories

COPY CONTROL INTERFACE KIT-A1  
SERIAL INTERFACE KIT-K3  
CONNECTION KIT-A2 FOR BLUETOOTH LE  
NFC KIT-E1

### Fax Accessories

SUPER G3 FAX BOARD-BF1  
SUPER G3 2ND LINE FAX BOARD-BF1  
SUPER G3 3RD/4TH LINE FAX BOARD-AS1  
REMOTE FAX KIT-A1  
IP FAX EXPANSION KIT-B1

## Other Options

### Accessibility Accessories

ADF ACCESS HANDLE-A1  
VOICE GUIDANCE KIT-G1  
VOICE OPERATION KIT-D1

### Consumables

STAPLE-P1  
STAPLE CARTRIDGE-Y1

For full specifications, please refer to the specification table on your local Canon web site.

# MAIN CONFIGURATION OPTIONS



## PLATEN COVER Y2

- Single document scanning

## DADF-BA1

- Multiple document scanning
- 100-sheet duplexing automatic document feeder
- Scans up to 70 ipm (1-sided, 300dpi) and 35ipm (2-sided, 300dpi)

## SINGLE-PASS DADF-C1

- Single-Pass DADF-C1
- Multiple document scanning 200-sheet duplexing automatic document feeder
- Scans up to 135 ipm (1-sided, 300 dpi) and 270 ipm (2-sided, 300 dpi)



## BOOKLET FINISHER-Y1

- 2-tray, 3,250 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports ECO-Staple 4 sheets (80 gsm) and Staple-On-Demand 50 sheets (80 gsm)
- Support optional external 2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1



## INNER 2 WAY TRAY-L1

- Separates copies, prints and faxes
- Adds a second internal output tray



## BUFFER PASS UNIT-N1

- Transports paper to external finisher



## INNER FINISHER-J1

- 2-tray, 545-sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Stapling 4 sheets (80 gsm) and Staple-On-Demand 40 sheets (80 gsm)
- Supports optional Inner 2/3H Puncher-C1 and 2/F4H Puncher-C1



## STAPLE FINISHER-Y1

- 2-tray, 3,250 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Staple 4 sheets (80 gsm) and Staple-On-Demand 50 sheets (80 gsm)
- Support optional external 2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1



## UTILITY TRAY-B1



## PAPER DECK UNIT-F1

- Supports up to A4
- Media weight 60-128gsm
- 2,700 sheets (80gsm)



## HIGH CAPACITY CASSETTE FEEDING UNIT-B1

- Supports up to A4
- Media weight 60-128gsm
- 2,450 sheets (80gsm)



## CASSETTE FEEDING UNIT-A1

- Supports up to A3
- Media weight 60-128gsm
- 2 x 550 sheets (80gsm)

## METAL PEDESTAL 45/25

Raises the device, no additional media supply



To arrange for a demonstration, simply contact any of our offices below.

**SOUTH & SOUTHEAST ASIA  
REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #15-01 Galaxis Singapore 138522  
Tel: 65-6799 8888 | Fax: 65-6799-8882 | [www.canon-asia.com](http://www.canon-asia.com) | [www.canon.com.sg](http://www.canon.com.sg)

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, iW, Business can be simple and get Smart get genuine are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte Ltd.

Adobe, PostScript, PostScript 3 and the PostScript logo are trademarks of Adobe Systems Incorporated

0220W385 © 2020 Canon Singapore Pte. Ltd.  
All rights reserved. Printed in Singapore.