

PERFORMANCE WITHOUT COMPROMISE

Experience superior performance and quality prints with the compact imageRUNNER C3322L. With simple and easy to use touch operations, users can complete routines with just one click, allowing users to focus on task that matters.




EFFORTLESS NAVIGATION



5 inch touch panel



User-friendly touchscreen interface



Customisable shortcuts via Application Library

PRODUCTIVITY



Direct print and save files on USB Memory Devices



One touch button operation to ease daily tasks



Robust paper-handling capacity of up to 960 sheets**

**A4, 80 gsm

MOBILE PRINTING



QR Code for easy pairing with device



Print/Scan easily with Canon PRINT Business Application



SECURITY



uniFLOW Online/Online Express



Data and document protection



Device and network protection



Encrypted Secure Print



Automatic recovery

SPECIFICATION

MAIN UNIT	
Machine Type	A3 Colour Laser Multifunctional
Core Functions	Print, Copy, Scan and Send
Control Panel	5 inch TFT LCD WVGA Colour Touch Panel
Memory	1.0GB RAM
Storage	eMMC: 2GB
Interface Connection	Network 100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Others USB 2.0 (Host) x2, USB 2.0 (Device) x1
Paper Supply Capacity (A4, 80 gsm)	Standard: 960 sheets (480-sheets Paper Cassette x 2) Maximum: 960 sheets
Paper Output Capacity (A4, 80 gsm)	Standard: 250 Sheets Maximum: 250 Sheets
Finishing Capabilities	Collate, Group
Supported Media Types	Upper/Lower Cassette: Plain, Recycled, Colour, Pre-punched
Supported Media Sizes	Upper Cassette: Standard Size: A4 Lower Cassette: Standard Size: A3, A4, A4R, A5R Custom Size: 139.7 x 210.0 mm to 297.0 x 431.8 mm
Supported Media Weights	Upper/Lower Cassette: 64 to 90 gsm Duplex: 64 to 90 gsm
Warm-up Time	1.4.2 seconds or less* <i>*Time from device power on to when copy icon appears and is enabled to operate on the touch panel display.</i> From Sleep Mode: 10 seconds or less From Power On: 19 Seconds or less <i>*Time from device power on, until copy ready (not print reservation)</i>
Dimensions (W X D X H)	565 x 653 x 863 mm (with DADF-AZ2)
Installation Space (W X D)	Basic: 940 x 1,106 mm (with DADF-AZ2 + right door & paper cassette opened)
Weight	With Platen Cover-AA2: Approx. 65 kg including toner With DADF-AZ2: Approx. 70 kg including toner
PRINT SPECIFICATIONS	
Print Speed (BW/CL)	Up to 22 ppm / 22 ppm (A4), Up to 12 ppm / 12 ppm (A3, A4R)
Print Resolution (dpi)	600 x 600 1200 x 1200 (half-speed)
Page Description Languages	UFR II
Mobile and Cloud Applications	AirPrint, Mopria, Canon PRINT Business and uniFLOW Online and Universal Print
Operating System	UFR II: Windows® 10/11 / Server2012 / Server2012 R2 / Server2016 / Server2019 / Server2022, macOS (10.13 or later)
COPY SPECIFICATIONS	
Copy Speed	Up to 22/22 ppm (A4), Up to 12/12 ppm (A3, A4R)
First-Copy-Out-Time (A4, BW/CL)	Approx. 6.9 / 9.8 seconds or less
Copy Resolution (dpi)	600 x 600: BW 300 x 600: Colour 300 x 300: Colour (Speed Priority mode)
Multiple Copies	Up to 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	Variable zoom: 25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100%(1:1), 115%, 122%, 141%, 200%, 400%

SCAN SPECIFICATIONS	
Type	Optional: DADF-AZ2 [2-sided to 2-sided] or Platen Cover-AA2
Document Feeder Paper Capacity (80 gsm)	DADF-AZ2: Up to 50 sheets
Acceptable Originals and Weights	Platen: Sheet, Book and 3-Dimensional objects Document Feeder media weight: 1-sided scanning: 38 to 128 gsm 2-sided scanning: 52 to 128 gsm
Supported Media Sizes	Platen: Max. scanning size: 297.0 x 431.8 mm Document Feeder Media Size: A3, A4, A4R, A5, A5R, B4, B5, B5R Custom Size: 128.0 x 148.0 mm to 297.0 x 431.8 mm
Scan Speed (BW/CL; A4)	DADF-AZ2: 1-sided Scanning: Up to 30 ipm / 30 ipm (300 x 300 dpi, send) Up to 25 ipm / - (600 x 600 dpi, copy) 2-sided Scanning: Up to 10 ipm / 10 ipm (300 x 300 dpi, send) Up to 8 ipm / - (600 x 600 dpi, copy)
Scan Resolution (dpi)	Scan for Copy: Up to 600 x 600 Scan for Send: Push: BW: up to 600 x 300, CL: Up to 300 x 600 Pull: BW: up to 600 x 600, CL: Up to 300 x 600
Pull Scan Specifications	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows®10/11/macOS (10.13 or later)
SEND SPECIFICATIONS	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB, FTP
Address Book	LDAP (50)/Local (300)/One-touch (281)
Send Resolution (dpi)	Push: 300 x 300* (E-mail/SMB/FTP), 192 x 204 (IFAX) <i>*Colour PDF: 200 x 200</i> Pull: 50 x 50, 75 x 75, 100 x 100, 150 x 150, 200 x 200, 300 x 300, 400 x 400*, 600 x 600* (Users can set resolution by 1dpi between 25 to 9600) <i>*colour mode is black and white only</i>
Communication Protocol	File: FTP (TCP/IP), SMB3.0 (TCP/IP) E-mail/Fax: SMTP(send), POP3(receive)
File Format	Standard: TIFF (MMR), JPEG*, PDF (Compact, OCR (Text Searchable) Encrypt, Device Signature) <i>*Single page only</i>
ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80% RH (Relative Humidity)
Power Source	220-240V 50/60Hz, 5A
Power Consumption	Maximum: Approx. 1,500 W Sleep Mode: Approx. 0.8 W* <i>*Sleep mode is not available in all circumstances due to certain settings.</i>
CONSUMABLES	
Toner Yield (Estimated @ 5% Coverage)	NPG-88 Toner BK: 38,000 pages NPG-88 Toner C/M/Y: 25,000 pages NPG-88L Toner C/M/Y: 4,000 pages
HARDWARE ACCESSORIES	
DADF-AZ2, Platen Cover- AA2, ADF Access Handle-A1	

Canon
Delighting You Always

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

CANON SINGAPORE PTE. LTD.

1 Fusionpolis Place #14-10 Galaxis, Singapore 138522
Tel: 65-6799-8888 | Fax: 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

0856-20-8000-5

e-mail: canon@canondistributor.com
web: <https://canondistributor.com>