



Dependable and versatile with enhanced security

The imageRUNNER ADVANCE DX 4900i series aims to digitally transform workplaces with its outstanding reliability and enhanced security features. Together with intuitive usability and various options, this series will be ideal for various workplace requirements.

WORKFLOW EFFICIENCY

- Intuitive touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Industry leading Single-Pass document feeder option to allow up to 270 ipm scanning, supports paper skew prevention and comes with advanced anti-dust/streak measures.
- My ADVANCE enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.
- Various finishing functions such as Staple-on-Demand, ECO-Staple, saddle stitch, double/corner stapling and foldings are available as an option.

COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, resulting in lower total document cost.
- Seamless integration with output management solutions, such as uniFLOW or uniFLOW Online Express for detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.

QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies contribute to high-quality output to meet the needs of busy department.
- State-of-the-art imaging technologies and toner allow for consistent images in rich black-and-white tones and 1,200-dpi print resolution.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Standard PCL and optional Adobe PostScript 3 print driver allows seamless integration with enterprise applications.
- Remote diagnostics allow timely, accurate and effective resolution.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

SUSTAINABILITY

- Fusing technologies and innovative sleep mode features help lower overall energy consumption.
- Minimise paper wastage by holding jobs at the device with Force Hold Print. Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.
- Consumes as little as 0.8W in sleep mode.

SECURITY

- Control who has access to the device with different authentication methods such as picture login, department ID, user authentication and card access.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.
- System verification at startup and McAfee® Embedded Control ensures device security, protecting against malware and tampering of firmware.
- Integrate with third-party solutions for complete monitoring protection.

MACHINE SPECIFICATION

MAIN UNIT

Type

A3 Monochrome Laser Multifunctional

Core Function

Print, Copy, Scan, Send, Store and Optional Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Colour Touch Panel

Memory

RAM: Main CPU: 2GB
Image Processing CPU: 1GB + 0.5GB

Storage

Standard : (SSD) 256GB
Optional : (SSD) 1TB

Interface Connection

Network

Standard : 1000Base-T/100Base-TX/10Base-T
Optional : Wireless LAN (IEEE 802.11 b/g/n)

Others

Standard : USB 2.0 x1 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)

Optional : Serial Interface, Copy Control Interface

Paper Supply Capacity (A4, 80gsm)

Standard : 1,200 sheets (2x 550-sheet cassettes,
1x 100-sheet multi-purpose tray)
Maximum : 3,650 sheets (with High Capacity Cassette
Feeding Unit-E1)

Paper Output Capacity (A4, 80gsm)

Standard : 250 Sheets
Maximum : 3,450 Sheets (with Staple Finisher-AE1 or Booklet
Finisher-AE1 and Copy Tray-T2)

Finishing Capabilities

Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch,
Eco Staple, Staple On Demand

* Finishing capabilities vary depending on the options connected.

Supported Media Types

Multi-Purpose Tray:
Thin, Plain, Heavy, Recycled, Coated*, Colour, Tracing, Bond,
Transparency, Labels, Pre-punched, Letterhead, Envelope,
Postcard

* SRA3 is unsupported for Coated (257 to 300 gsm).

Upper Cassette:

Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency,
Pre-punched, Letterhead, Envelope*, Postcard

* Envelope Feeder Attachment Kit B (standard) is required except ISO-C5.

Lower Cassette:

Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-
punched, Letterhead, Envelope*, Postcard

* Envelope Feeder Attachment A (standard) is required.

Supported Media Sizes

Multi-Purpose Tray:

Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5,
B5R, Foolscap, India Legal, F4A

Custom Size: 98.4 x 139.7 mm to 320.0 x 457.2 mm

Free size: 100.0 x 148.0 mm to 304.8 x 457.2 mm

Envelope: COM10 No.10, Monarch, ISO-C5, DL

Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm

Upper Cassette:

Standard size : A4, A5, A5R, A6R, B5

Custom size : 105.0 x 148.0 mm to 297.0 x 215.9 mm

Envelope : ISO-C5

Lower Cassette:

Standard size : A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R,
Foolscap, India Legal, F4A

Custom size : 105.0 x 148.0 mm to 304.8 x 457.2 mm

Envelopes* : COM10 No.10, Monarch, DL

* Envelope Attachment A (standard) is required.

Supported Media Weights

Multi-purpose tray : 52 to 300 gsm*

Upper/Lower Cassette: 52 to 256 gsm

Duplex : 52 to 220 gsm

* SRA3 is unsupported for Coated (257-300gsm). Media Adjustment Kit-A1
is required for Coated (257-300gsm)

Warm-up Time (Quick start mode: ON)

Quick Startup Mode : 4 seconds or less*

From Sleep Mode : 10 Seconds or Less

From Power On : 10 Seconds or Less*

+ Time from device power-on to when the copy icon appears and is enabled to
operate on the touch panel display.

* Time from device power-on, until copy ready (not print reservation)

Dimensions (W x D x H)

With Platen Cover-Y3 : 565 x 692 x 788 mm

With Single Pass DADF-C1 : 565 x 722 x 897 mm

With DADF-BA1 : 565 x 719 x 891 mm

Installation Space (W x D)

Basic: 978 x 1,119 mm (with Single Pass DADF-C1 + right door
& multi-purpose tray opened + paper cassette
opened)

978 x 1,116 mm (with DADF-BA1 + right door & multi-
purpose tray opened + paper cassette opened)

Fully Configured:

1,651 x 1,119 mm (with Single Pass DADF-C1 + Staple
Finisher-AE1/Booklet Finisher-AE1 + Copy Tray-T2
extended + paper cassette opened)

1,651 x 1,116 mm (with DADF-BA1 + Staple Finisher-
AE1/Booklet Finisher-AE1 + Copy Tray-T2 extended +
paper cassette opened)

Weight (including toner)

With Platen Cover-Y3 : Approx. 62.0 kg

With DADF-BA1 : Approx. 69.0 kg

With Single Pass DADF-C1 : Approx. 75.0 kg

Printing Specifications

Print Speed (BW, 1-sided)

iR-ADV DX 4945i: Up to 45 ppm (A4),
Up to 22 ppm (A3),
Up to 32 ppm (A4R)

iR-ADV DX 4935i: Up to 35 ppm (A4),

Up to 17 ppm (A3),

Up to 23 ppm (A4R)

iR-ADV DX 4925i: Up to 25 ppm (A4),

Up to 15 ppm (A3),

Up to 20 ppm (A4R)

Print Resolution (dpi): 1,200 x 600,
1,200 x 1,200 (half-speed)

Page Description Languages

Standard : UFR II, PCL 6

Optional : Adobe PostScript 3

Direct Print (RUI)

Supported file types: PDF, EPS, TIFF/JPEG and XPS

Printing From Mobile and Cloud

AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and
Universal Print

Fonts

PS fonts: 136 Roman

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T* (Japanese, Korean,
Simplified and Traditional Chinese),
Barcode fonts*²

*1 Requires optional PCL INTERNATIONAL FONT SET-A1

*2 Requires optional BARCODE PRINTING KIT-D1

Operating System

UFR II : Windows® 10/11/Server2012/Server2012 R2/Server2016/
Server2019/Server2022, macOS(10.13 or later)

PCL : Windows® 10/11/Server2012/Server2012 R2/Server2016/
Server2019/Server2022

PS : Windows® 10/11/Server2012/Server2012 R2/Server2016/
Server2019/Server2022, macOS(10.13 or later)

PPD : Windows® 10/11, macOS(10.13 or later)

Copy Specifications

Copy Speed (BW, 1-sided)

iR-ADV DX 4945i: Up to 45 ppm (A4),

Up to 22 ppm (A3),

Up to 32 ppm (A4R)

iR-ADV DX 4935i: Up to 35 ppm (A4),

Up to 17 ppm (A3),

Up to 23 ppm (A4R)

iR-ADV DX 4925i: Up to 25 ppm (A4),

Up to 15 ppm (A3),

Up to 20 ppm (A4R)

First-Copy-Out Time (A4)

iR-ADV DX 4945i : 4.6 seconds

iR-ADV DX 4935i : 5.5 seconds

iR-ADV DX 4925i : 6.1 seconds

Copy Resolution (dpi) 600 x 600

Multiple Copies Up to 9,999 copies

Copy Density Automatic or Manual (9 Levels)

Magnification

Variable zoom: 25% - 400% (1% Increments)
Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%

Scan Specifications

Type

Standard : Colour Flatbed Scan Unit
Optional : Platen Cover Type-Y3, Single Pass DADF-C1* or DADF-BA1 [2-sided to 2-sided (Automatic with DADF)]

* Detect Feeder Multi Sheet Feed is supported.

Document Feeder Paper Capacity (80gsm)

Single Pass DADF-C1 : up to 200 sheets
DADF-BA1 : up to 100 sheets

Acceptable Originals and Weights

Platen: Sheet, Book, and 3-Dimensional objects

Document Feeder media weight:

SINGLE PASS DADF-C1*:

1-sided scanning : 38 to 220 gsm (BW, CL)

2-sided scanning : 38 to 220 gsm (BW, CL)

*Acceptable weights of A6R or smaller is 50 to 220gsm.

DADF-BA1:

1-sided scanning : 38 to 128 gsm (BW), 64 to 128 gsm (CL)

2-sided scanning : 50 to 128 gsm (BW), 64 to 128 gsm (CL)

Supported Media Sizes

Platen: max. scanning size: up to 297.0 x 431.8 mm

Single Pass DADF-C1: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R,

Custom size: 69.9 x 139.7 mm to 304.8 x 431.8 mm

DADF-BA1: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6,

Custom size: 139.7 x 128 mm to 297.0 x 431.8 mm

Scan Speed (ipm: BW/CL; A4)

Single Pass DADF-C1:

1-sided Scanning : 135/135 (300 x 300 dpi, send),
80/- (600 x 600 dpi, copy)

2-sided Scanning : 270/270 (300 x 300 dpi, send),
160/- (600 x 600 dpi, copy)

DADF-BA1:

1-sided Scanning : 70/70 (300 x 300 dpi, send),
51/- (600 x 600 dpi, copy)

2-sided Scanning : 35/35 (300 x 300 dpi, send),
25.5/- (600 x 600 dpi, copy)

Scan Resolution (dpi)

Scan for Copy : 600 x 600

Scan for Send : (Push) 600 x 600 (SMB/FTP/WebDAV/
iFAX), (Pull) 600 x 600

Scan for Fax : 600 x 600

Pull Scan Specifications

Color Network ScanGear2. For both TWAIN and WIA

Supported OS: Windows® 10/11/Server2012/Server2012 R2/
Server 2016/Server 2019/Server 2022

Send Specifications

Destination

Standard : E-mail/Internet FAX (SMTP), SMB, FTP,
WebDAV, Mail Box
Optional : Super G3 FAX, IP Fax

Address Book

LDAP (2,000)/Local (1,600)/One-touch (200)

Send Resolution (dpi)

Push : up to 600 x 600

Pull : up to 600 x 600

Communication Protocol

File : FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV
E-mail/i-Fax : SMTP (send), POP3 (receive)

File Format

Standard : TIFF (MMR), JPEG*, PDF (Compact, OCR (Text Searchable), Optimize PDF for Web, Format to PDF/A-1b, Trace & Smooth, Encrypt), XPS (Compact, OCR (Text Searchable)), PDF/XPS (Device Signature, User Signature), Office Open XML (PowerPoint, Word)

* Single-Page only

Fax Specifications

Maximum Number of Connection Lines 4

Modem Speed : Super G3 : 33.6 kbps
G3 : 14.4 kbps

Compression Method : MH, MR, MMR, JBIG

Resolution (dpi):

400x400 (Ultra Fine), 200x400 (Super Fine),
200x200 (Fine), 200x100 (Normal)

Sending/Recording Size

Sending : A3, A4, A4R, A5*1, A5R*1, B4, B5*2, B5R*1

Receiving : A3, A4, A4R, A5, A5R, B4, B5, B5R

*1 Sent as A4 *2 Sent as B4 short

FAX Memory : Up to 30,000 pages (2,000 jobs)

Speed Dials : Max. 200

Group Dials/Destinations : Max. 199 dials

Sequential Broadcast : Max. 256 addresses

Memory Backup : Yes

Store Specifications

Mail Box (Number supported)

100 User Inboxes, 1 Memory RX Inbox,

50 Confidential Fax Inboxes

Maximum 30,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported Client PC: Windows® 10/11

Concurrent Connections (Max.): SMB: 64, WebDAV: 3

Advanced Box available disc space

Standard: 16GB

(With option: max. 480GB)

Security Specifications

Authentication and Access Control

User Authentication: Picture Login, Picture and PIN Login,
Card Login, Username and Password Login, Function Level
Login, Mobile Login

Department ID Authentication: Department ID and PIN

Login, Function Level Login

uniFLOW Online Express: PIN Login, Picture Login, Picture
and PIN Login, Card Login, Card and PIN Login, Username
and Password Login, Department ID and PIN Login,
Function Level Login

Access Management System: Access Control

Document Security

Print Security: Secure Print, Encrypted Secure Print, Forced
Hold Printing, uniFLOW Secure Print*

Receive Data Security: Confidential Fax Inbox Forwarding
Received Documents Automatically

Scan Security: Encrypted PDF, Device Signature PDF/
XPS, User Signature PDF/XPS, Adobe LiveCycle Rights
Management ES2.5 Integration

BOX Security: Mail Box Password Protected, Advanced Box
Access Control

Send Data Security: Setting for requesting password input
per transmission, Restricted E-mail/File send functions,
Confirming FAX number, Allow/Restrict Fax Driver
Transmissions, Allow/Restrict Sending from History, S/MIME
Support

Document Tracking: Secure Watermark

* Requires uniFLOW Online/uniFLOW

Network Security

TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0,
Firewall Functionality (IP/MAC Address Filtering), WPA3
support (Wi-Fi), Dual Network Support (Wired LAN/
Wireless LAN, Wired LAN/Wired LAN), Disabling Unused
Functions (Enabling/Disabling Protocols/Applications,
Enabling/Disabling Remote UI, Enabling/Disabling USB
Interface), Communication Line Separation (G3 FAX, USB
Port, Advanced Box, Scan and Send -Virus Concerns for
E-mail Reception)

Device Security

Protecting SSD Data [SSD Data Encryption (FIPS140-
2 Validated), SSD Lock], Standard SSD Initialize, Trusted
Platform Module (TPM), Job Log Conceal Function,
Checking MFD Software Integrity (Verify System at Startup,
Automatic Recovery, Runtime Intrusion Detection),
Common Criteria Certification (HCD-PP) (pending
confirmation)

Device Management and Auditing

Administrator Password, Digital Certificate And Key
Management, Audit Log, Cooperating with External
Security Audit System (Security Information and Event
Management), Image Data Logging, Security Policy Setting

Environmental Specifications

Operating Environment

Temperature: 10 to 30 °C

Humidity: 20 to 80 % RH (Relative Humidity)

Power Source : 220-240V, 50-60Hz, 5A

Power Consumption

Maximum: Approx. 1,500W

Sleep mode: Approx. 0.8 W*

* 0.8 W sleep mode is not available in all circumstances due to certain
settings.

Consumables

Toner Cartridge : NPG-89 Toner BK
Toner Yield (Estimated Yield @6% Coverage)
: 44,500 pages

Software and Printer Management

Tracking and Reporting

uniFLOW Online Express/uniFLOW Online

Remote Management Tools

iW Enterprise Management Console
eMaintenance
Content Delivery System

Scanning Software

Color Network ScanGear 2

Optimisation Tools

Canon Driver Configuration Tool

Platform

MEAP (Multifunctional Embedded Application Platform)

Document Publishing

IW DESKTOP

Paper Supply Options

CASSETTE FEEDING UNIT - AW1

Paper Capacity : 550 Sheets x 2 (80gsm)

Paper Type : Thin, Plain, Recycled, Colour, Heavy,
Bond, Transparency, Pre-punched,
Letterhead, Postcard

Paper Size : A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R

Custom size : 105.0 x 148.0 mm to 304.8 x 457.2 mm

Paper Weight : 52 to 256 gsm

Power Source : From the Main Unit

Dimensions (WxDxH) : 565 x 635 x 248 mm

Weight : Approx. 16.0 kg

HIGH CAPACITY CASSETTE FEEDING UNIT - E1

Paper Capacity : 2,450 sheets (80 gsm)

Paper Type : Thin, Plain, Recycled, Colour, Heavy,
Bond, Pre-punched, Letterhead

Paper Size : A4

Paper Weight : 52 to 256 gsm

Power Source : From the Main Unit

Dimensions (WxDxH) : 565 x 650 x 248 mm

Weight : Approx. 28.0 kg

Hardware Accessories

Card Readers

IC CARD READER BOX FOR NUMERIC KEYPAD-A1

Others

UTILITY TRAY-B1

NUMERIC KEYPAD-A2

MEDIA ADJUSTMENT KIT-A1

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1

PS PRINTER KIT-BG1

BARCODE PRINTING KIT-D1

Fax Accessories

SUPER G3 FAX BOARD-BH1

SUPER G3 2ND LINE FAX BOARD-BH2

SUPER G3 3RD/4TH LINE FAX BOARD-AX1

REMOTE FAX KIT-A1

IP FAX EXPANSION KIT-B1

Storage Accessories

1TB SSD-A1

MEMORY MIRRORING KIT-A1

250GB SSD-A1

Interface Accessories

WIRELESS LAN BOARD-F1

COPY CONTROL INTERFACE KIT-A1

SERIAL INTERFACE KIT-K3

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1

VOICE GUIDANCE KIT-G1

VOICE OPERATION KIT-D1

Staple Cartridges

STAPLE-P1

STAPLE CARTRIDGE-Y1

For full specifications, please refer to the specification
table on your local Canon web site.

MAIN CONFIGURATION OPTIONS



BOOKLET FINISHER-AE1

- 2-tray, 3,250 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports ECO-Staple 8 sheets (80 gsm) and Staple-On-Demand 50 sheets (80 gsm)
- Support optional external 2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1



STAPLE FINISHER-AE1

- 2-tray, 3,250 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Staple 8 sheets (80 gsm) and Staple-On-Demand 50 sheets (80 gsm)
- Support optional external 2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1



INNER 2 WAY TRAY-M1

- Separates copies, prints and faxes
- Adds a second internal output tray



INNER FINISHER-L1

- 2-tray, 545-sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Stapling 8 sheets (80 gsm) and Staple-On-Demand 40 sheets (80 gsm)
- Supports optional Inner 2/3H Puncher-D1 and 2/F4H Puncher-D1



PLATEN COVER Y3

- Single document scanning



DADF-BA1

- Multiple document scanning
- 100-sheet duplexing automatic document feeder
- Scans up to 70 ipm (1-sided, 300dpi) and 35ipm (2-sided, 300dpi)



SINGLE-PASS DADF-C1

- Multiple document scanning
- 200-sheet duplexing automatic document feeder
- Scans up to 135 ipm (1-sided, 300 dpi) and 270 ipm (2-sided, 300 dpi)



UTILITY TRAY-B1



HIGH CAPACITY CASSETTE FEEDING UNIT-E1

- Supports up to A4
- Media weight 52 -256 gsm
- 2,450 sheets (80gsm)



CASSETTE FEEDING UNIT-AW1

- Supports up to A3
- Media weight 52 -256 gsm
- 2 x 550 sheets (80gsm)

METAL PEDESTAL 38

Raises the device, no additional media supply



Adobe PostScript

Partner/Dealer Stamp

0856-20-8000-5

e-mail: canon@canondistributor.com

web: <https://canondistributor.com>

To arrange for a demonstration, simply contact our office below.

**SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #14-10 Galaxis Singapore 138522
Tel: 65-6799 8888 | Fax: 65-6799-8882 | <https://asia.canon/> | <https://sg.canon/>

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageRUNNER ADVANCE, MEAP, eMaintenance, iW and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW is an independent party software distributed by Canon Singapore Pte Ltd.

Adobe, LiveCycle, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

2023 Canon Singapore Pte. Ltd.
All rights reserved. Printed in Singapore.